

\$





The professional single-phase pressure washer with a robust, appealing design

The CI C20 single-phase cold pressure washer stands out for its appealing, robust design. Featuring compact dimensions and extreme manoeuvrability, it moves easily, even around obstacles or on stairs.

The CI C20 is a **high-pressure washer** that is extremely manoeuvrable and easy to use. Its innovative V-shaped handlebars are wide and ergonomic to facilitate grip during use.

High performing and powerful, the CI C20 is a **professional cold pressure washer** suited to working in even the mostly stressful conditions for long periods. Thanks to its high pressure and notable flow rate, this power washer is able to best satisfy the cleaning needs of the automotive, industrial, logistics and handicraft sectors.

THE ADVANTAGES OF CI C20

Many are the benefits CI C20 can offer:

- Trolley cold pressure washer with two large wheels that enhance manoeuvrability and transportability
- New concept ergonomic handlebars with a handlegrip designed to facilitate the use of the pressure washer
- Powerful induction motor that makes the pressure washer highly performing, efficient and reliable
- The low motor rotation speed of only 1450 rpm ensures high durability over time, even during extended sessions
- Ceramic 3-piston pump with crank-rod system and brass head for high performance
- Automatic safety valve with pressure shut-off at pump head

- Single-phase electric induction motor with heat protection that guarantees maximum efficiency and durability
- Adjustable pressure
- Built-in manometer
- Built-in adjustable detergent suction
- Inspectionable water feed filter
- Stop&Go: when the machine is temporarily idle, it stops so as to optimize consumption and reduce waste
- Comes with professional accessories: gun with protection and Swivel coupling, lance with interchangeable nozzle
- 10-metre reinforced high pressure tube
- Built-in accessory holder on machine



TECHNICAL DESCRIPTION		CI C20
Max pressure	bar/psi	150/2200
Max flow rate	l/h	630
Туре	-	cold water
Power consumption	KW	3,0
Power supply	V/Hz	230/50
Motor	type/hp	single-phase electric induction
Rotation speed	rpm	1450
Pump	type	ceramic piston with crank-rod system
Pump head	material	brass
Net weight	Kg	43,6
Machine dimensions (Lxhxw)	mm	800x980x470



COMAC S.p.A. Via Maestri del Lavoro, 13 - 37059 Santa Maria di Zevio - Verona - ITALY Tel. 045 8774222 - www.comac.it - com@comac.it

Comac S.p.A. org. cert. ISO 9001:2015, ISO 14001:2015, ISO 45001:2018, SA 8000:2014

