

R C





The CI H20 EM INOX is a **professional hot pressure washer** featuring a compact structure and a robust stainless steel body. It is also very easy to handle, thanks to the four large wheels that facilitate the transport of this **high-pressure washer**.

CI H20 EM INOX is equipped with a powerful single-phase electric motor with magnetothermic protection that makes this hot water pressure washer performing, powerful and reliable in any condition of use.

Equipped with a high efficiency stainless steel hot box powered by fuel oil, the CI H20 EM INOX can supply hot water with a temperature of up to 150°C, therefore making it perfect for removing even the most stubborn dirt.

The components and technologies installed on this **professional pressure washer** allow it to guarantee a high performance and great durability over time. Because of this, the CI H20 EM INOX is therefore the perfect for the food, handicraft, industrial, and transport sectors.

## THE ADVANTAGES OF CI H20 EM INOX

Many are the benefits CI H20 EM INOX can offer:

- Hot pressure washer with four large wheels with rubber treads that facilitate manoeuvrability and transportability
- Robust structure with stainless steel cover (AISI 430)
- Powerful single-phase electric motor with thermal-magnetic protection that makes the pressure washer highly performing, efficient and reliable
- Ceramic 3-piston pump with crank-rod system and brass head for high performance
- Automatic safety valve
- 3 24V pressure switches
- High efficiency stainless steel (AISI 430) hot box powered by fuel oil
- Adjustable pressure
- 150°C thermostat
- Stop&Go: when the machine is temporarily idle, it stops so as to

optimize consumption and reduce waste

- Switch-off system for: micro leaks, no water or if the motor overheats
- Low-voltage instrument panel
- Error, fuel oil, voltage and stop warning lights
- 24-litre fuel oil tank
- Built-in adjustable detergent suction
- Inspectionable water feed filter
- Comes with professional accessories: gun with protection and Swivel coupling, wand with high/low pressure head
- $\frac{1}{4}$  '' MEG type nozzle with flat jet
- 10-metre reinforced high pressure tube
- Accessory holder and tube storage on the side



TECHNICAL DESCRIPTION		CI H20 EM INOX
Max pressure	bar/psi	150/2200
Max flow rate	l/h	600
Туре	-	hot water
∆°t	°C	55
Power consumption	KW	3,0
Power supply	V/Hz	230/50
Motor	type/hp	single-phase electric with thermal-magnetic protection
Rotation speed	rpm	1450
Pump	type	ceramic piston with crank-rod system
Pump head	material	brass
Net weight	Kg	80
Machine dimensions (lxhxw)	mm	1100x700x650



COMAC S.p.A. Via Maestri del Lavoro, 13 - 37059 Santa Maria di Zevio - Verona - ITALY Tel. 045 8774222 - www.comac.it - com@comac.it

Comac S.p.A. org. cert. ISO 9001:2015, ISO 14001:2015, ISO 45001:2018, SA 8000:2014

equipment. - AB - 04/23 - Copyright © COMAC 2023

